

FOUR SEASONS Refrigeration Oil 59000
Recommended for Automotive Air Conditioning Compressors

FOUR SEASONS PN 59000
LFK INDUSTRIES, INC. - WAX-FREE MINERAL REFRIGERANT OIL

5/28/08

=====
MATERIAL SAFETY DATA SHEET

Revised: 12/01/99 MSDS ID: 59000 LFK Industries, Inc. Page 1
=====

=====
Section 1 - PRODUCT AND COMPANY IDENTIFICATION
=====

Product Name: 59000 Wax-Free Mineral Refrigerant Oil

MANUFACTURER:

LFK Industries, Inc.
519 Gibson St
Seagoville, TX 76016

Telephone Number:
972-287-1200

=====
Section 2 - HAZARDOUS INGREDIENTS
=====

Case Number: 64742-52-5

Ingredient Name: Severely Hydrotreated Heavy Naphthenic Petroleum Oil

Exposure Limit: Oil Mist

OSHA PEL MIST 5 MG/M3 8 HRS
ACGIH TLV MIST 5 MG/M3 8 HRS

Concentration Percent by Volume: 100%

=====
Section 3 - HAZARDS IDENTIFICATION
=====

EMERGENCY OVERVIEW:

*** Not expected to cause a severe emergency hazard.

Potential Health Effects

Primary route(s) of entry: Skin

Eyes: Tests on similar materials suggest that no eye effect be expected.

Skin: Test on similar materials indicate that no significant adverse health effects are expected to occur upon short-term exposure.

Ingestion: Test on similar materials indicate that no significant adverse effects expected. Practically non-toxic.

Inhalation: Test on similar materials indicate that no significant adverse effects expected.

Chronic (Cancer Information): Prolonged and/or repeated contact with this material may produce skin irritation and inflammation.

=====

MATERIAL SAFETY DATA SHEET

Revised: 12/01/99 MSDS ID: 59000 LFK Industries, Inc. Page 3

=====

Fire Fighting Instructions: Use water to cool containers exposed to flames. Do not enter enclosed or a confined work space without proper protection equipment. Fire fighting personnel should wear respiratory protection (positive pressure if available). Products of combustion includes fumes, smoke and carbon monoxide.

=====

Section 6 - ACCIDENTAL RELEASE MEASURES

=====

Shut off ignition source. Contain spill and keep from entering waterways or sewers. Use personal protective equipment. Advise EPA; state agency if required. Absorb on inert material. Shovel, sweep or vacuum spill.

=====

Section 7 - HANDLING AND STORAGE

=====

Handling and storage precautions: Keep away from flames, sparks or hot services. Never use a torch to cut or weld on or near container. Empty oil containers can contain explosive vapors. NFPA Class IIIB storage. Wash thoroughly after handling.

Work/Hygienic Practices: Wash hands with soap and water before eating, drinking, smoking or use of toilet facilities. Do not use gasoline, solvents, kerosene, or harsh abrasive skin cleaners for washing exposed skin areas. Take a shower after work if general contact occurs. Remove oil-soaked clothing and launder before reuse. Launder or discard contaminated shoes and leather gloves.

=====

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

=====

Engineering Controls: Use adequate ventilation to keep oil mists of this material below applicable standard(s). See Section on occupational exposure limits.

Eye/Face Protection: Safety glasses or splash goggles. Have suitable eye wash water available.

Skin Protection: Avoid prolong and/or repeated skin contact. If prolonged contact cannot be avoided, wear protection impervious gloves and clothing. Acceptable materials for gloves are polyvinyl chloride; neoprene; nitrile; polyvinyl alcohol; viton.

Respiratory Protection: Normally not required if adequate ventilation. If occupational exposure limits are exceeded wear NIOSH/MSHA apparatus.

=====

MATERIAL SAFETY DATA SHEET

Revised: 12/01/99

MSDS ID: 59000 LFK Industries, Inc. Page 4

=====

Other/General Protection: If there is a likelihood of splashing, an oil resistant clothing should be worn. Never wear oil soaked clothing. Launder or dry clean before wearing. Discard oil soaked shoes. Affix warning labels on containers in accordance with 29 CFR 1910.1200 (Hazard Communication Standard).

=====

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

=====

Appearance: Clear, sale straw to water white, colored, viscous liquid

Odor: Light bland petroleum.

Odor Threshold: N.D.

Basic Physical Properties:

Physical State: Liquid
Boiling Point: .630 degrees F IBP .332 degrees C
Melting Point: N/A degrees F N/A degrees C
Vapor Pressure: <0.001 mm Hg @ 20 degrees C
Vapor Density: (Air=1): >5 Air=1
Specific Gravity: 0/91 Water=1
Molecular Weight: 420.00
Packing Density: N/A
Solubility (H2O): negligible in water
Percent Volatile: nil
Volatile Organic compounds (VOC) Content: 2.5%
Evaporation Rate: 1000X slower than ethyl ether
pH: essentially neutral
Viscosity: 517 SUC at 100 degrees F

=====

Section 10 - STABILITY AND REACTIVITY

=====

Stability: Stable.

Condition to Avoid (stability): Sources of ignition

Incompatible Materials: Strong oxidizers.

Hazardous decomposition Products: Combustion may produce carbon monoxide and other asphyxiants.

Hazardous polymerization: Will not occur.

=====

MATERIAL SAFETY DATA SHEET

Revised: 12/01/99 MSDS ID: 59000 LFK Industries, Inc. Page 5

=====

Section 11 - TOXICOLOGICAL INFORMATION

=====

Acute Studies: Test on similar materials show a low order of acute oral and dermal toxicity.

Eye Effects: Minimal irritation on contact.

Skin Effects: Practically non-toxic if absorbed. May cause mild irritation with prolonged and repeated contact.

Acute Oral Effects: Test on similar materials indicate low order of acute oral toxicity.

Acute Inhalation Effects: Low acute toxicity expected on inhalation.

This product is severely hydrotreated. Severely hydrotreated naphthenis petroleum oil has not been found to be carcinogenic or a potential carcinogen. This product is not listed as carcinogenic or a potential carcinogen by the National Toxicology Program, by the I.A.R.C. monographs or by OSHA.

=====

Section 12 - ECOLOGICAL INFORMATION

=====

No Data Given.

=====

Section 13 - DISPOSAL CONSIDERATIONS

=====

Follow federal, state and local regulation. Not a RCRA hazardous waste if uncontaminated. If "used", RCRA Criteria must be determined. Do not flush to drain/storm sewer. Contract to authorized disposal service. If permitted incineration may be practical. Recommend recycling.

RCRA Information: Not a RCRA hazardous waste if uncontaminated.

=====

Section 14 - TRANSPORT INFORMATION

=====

Proper Shipping Name: Not regulated by DOT.

Hazard Class: Not applicable.

DOT Identification Number: N/A

DOT Shipping Label: Not regulated by DOT.

