

# Material Safety Data Sheet

bp



10/10/2017

## 1. Chemical product and company identification

Product name CASTROL ATF +4 **CASTROL ATF+4 Automatic**  
MSDS # 464628 **TRANSMISSION FLUID**  
Historic MSDS #: 0000003533  
Code 464628-CA10  
Product use Automatic transmission fluid  
For specific application advice see appropriate Technical Data Sheet or consult our company representative.  
Manufacturer BP Lubricants USA Inc.  
1500 Valley Road  
Wayne, NJ 07470  
Telephone: (973) 633-2200  
Telecopier: (973) 633-7475  
EMERGENCY HEALTH INFORMATION: 1 (800) 447-8735  
Outside the US: +1 703-527-3887 (CHEMTREC)  
EMERGENCY SPILL INFORMATION: 1 (800) 424-9300 CHEMTREC (USA)  
OTHER PRODUCT INFORMATION 1 (866) 4 BP - MSDS  
(866-427-6737 Toll Free - North America)  
email: bpcares@bp.com

## 2. Composition/information on ingredients

Ingredient name	CAS #	% by weight
Highly refined mineral oil	Mixture	30 - 60

## 3. Hazards identification

Physical state Liquid.  
Color Red.  
Emergency overview CAUTION!  
MAY CAUSE EYE IRRITATION.  
MAY CAUSE SKIN IRRITATION.  
MAY CAUSE RESPIRATORY TRACT IRRITATION.  
Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Keep container closed. Use with adequate ventilation. Wash thoroughly after handling. Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis.  
Routes of entry Dermal contact. Eye contact. Inhalation. Ingestion.  
Potential health effects  
Eyes May cause eye irritation.  
Skin May cause skin irritation. Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis.  
Inhalation May cause respiratory tract irritation.  
Ingestion Ingestion may cause gastrointestinal irritation and diarrhea.

Product name CASTROL ATF +4

Product code 464628-CA10

Page: 1/5

Version 2 Date of issue 08/14/2006.

Format US

Language ENGLISH.

Build 4.2.8

( ENGLISH )

Medical conditions aggravated by over-exposure None identified.

See toxicological information (section 11).

#### 4. First aid measures

**Eye contact** In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention if irritation occurs.

**Skin contact** Immediately wash exposed skin with soap and water. Remove contaminated clothing and shoes. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention if irritation develops.

**Inhalation** If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

**Ingestion** Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If large quantities of this material are swallowed, call a physician immediately.

#### 5. Fire-fighting measures

**Flammability of the product** May be combustible at high temperature.

**Flash point** >190 °C (Open cup)

**Products of combustion** These products are carbon oxides (CO, CO<sub>2</sub>) (carbon monoxide, carbon dioxide), oxides of phosphorus, nitrogen oxides (NO, NO<sub>2</sub> etc.).

**Unusual fire/explosion hazards** This material is not explosive as defined by established regulatory criteria.

**Fire-fighting media and instructions** In case of fire, use water fog, foam, dry chemicals, or carbon dioxide. Do not use water jet.

**Protective clothing (fire)** Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

#### 6. Accidental release measures

**Personal precautions** Immediately contact emergency personnel. Keep unnecessary personnel away. Use suitable protective equipment (See Section: "Exposure controls/personal protection"). Follow all fire fighting procedures (See Section: "Fire-fighting measures").

**Environmental precautions and clean-up methods** If emergency personnel are unavailable, contain spilled material. For small spills add absorbent (soil may be used in the absence of other suitable materials) scoop up material and place in a sealed, liquid-proof container for disposal. For large spills dike spilled material or otherwise contain material to ensure runoff does not reach a waterway. Place spilled material in an appropriate container for disposal. Avoid contact of spilled material with soil and prevent runoff entering surface waterways. See Section 13 for Waste Disposal Information.

**Personal protection in case of a large spill** Splash goggles. Full suit. Boots. Gloves. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.

#### 7. Handling and storage

**Handling** Avoid contact with skin and clothing. Avoid prolonged or repeated contact with skin. Avoid contact with eyes. Use only with adequate ventilation. Avoid breathing vapor or mist. Wash thoroughly after handling.

**Storage** Keep container tightly closed. Keep container in a cool, well-ventilated area. Empty containers may contain harmful, flammable/combustible or explosive residue or vapors. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards.

Product name CASTROL ATF +4

Product code 464628-CA10

Page: 2/5

Version 2

Date of issue 08/14/2006.

Format US

Language ENGLISH.

Build 4.2.8

( ENGLISH )

## 8. Exposure controls/personal protection

### Occupational exposure limits

#### Ingredient name

Highly refined mineral oil

### Occupational exposure limits

#### ACGIH (United States).

STEL: 10 mg/m<sup>3</sup> 15 minute(s). Form: Oil mist, mineral

TWA: 5 mg/m<sup>3</sup> 8 hour(s). Form: Oil mist, mineral

#### OSHA (United States).

TWA: 5 mg/m<sup>3</sup> 8 hour(s). Form: Oil mist, mineral

### Control Measures

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits. Ensure that eyewash stations and safety showers are close to the work-station location.

### Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

### Personal protection

#### Eyes

Avoid contact with eyes. Chemical splash goggles.

#### Skin and body

Avoid contact with skin and clothing. Wear suitable protective clothing.

#### Respiratory

Use only with adequate ventilation. In accordance with good industrial hygiene and safety work practices, airborne exposures should be controlled to the lowest extent practicable.

#### Hands

Wear suitable gloves.

Consult your supervisor or S.O.P. for special handling directions

Consult local authorities for acceptable exposure limits.

## 9. Physical and chemical properties

### Physical state

Liquid.

### Odor

Mild. Petroleum

### Color

Red.

### Heat of combustion

Not available.

### Pour Point

-51 °C

### Specific gravity

0.848

### Density

848 kg/m<sup>3</sup> (0.848 g/cm<sup>3</sup>) at 15.6°C

### Solubility

Insoluble in cold water.

### Viscosity

Kinematic: 33 mm<sup>2</sup>/s (33 cSt) at 40°C

Kinematic: 7.5 mm<sup>2</sup>/s (7.5 cSt) at 100°C

### Viscosity Index

204

## 10. Stability and reactivity

### Stability and reactivity

The product is stable.

### Conditions to avoid

Keep away from heat, sparks and flame.

### Incompatibility with various substances

Reactive or incompatible with the following materials: oxidizing materials.

### Hazardous decomposition products

Products of combustion: carbon oxides (CO, CO<sub>2</sub>) (carbon monoxide, carbon dioxide), oxides of phosphorus, nitrogen oxides (NO, NO<sub>2</sub> etc.).

### Hazardous polymerization

Will not occur.

Product name CASTROL ATF +4

Product code 464628-CA10

Page: 3/5

Version 2

Date of issue 08/14/2006.

Format US

Language ENGLISH.

Build 4.2.8

( ENGLISH )

## 11. Toxicological information

### Chronic toxicity

#### Carcinogenic effects

No component of this product at levels greater than 0.1% is identified as a carcinogen by ACGIH or the International Agency for Research on Cancer (IARC). No component of this product present at levels greater than 0.1% is identified as a carcinogen by the U.S. National Toxicology Program (NTP) or the U.S. Occupational Safety and Health Act (OSHA).

#### Mutagenic effects

No component of this product at levels greater than 0.1% is classified by established regulatory criteria as a mutagen.

#### Reproductive effects

No component of this product at levels greater than 0.1% is classified by established regulatory criteria as a reproductive toxin.

#### Teratogenic effects

No component of this product at levels greater than 0.1% is classified by established regulatory criteria as teratogenic or embryotoxic.

## 12. Ecological information

### Ecotoxicity

No testing has been performed by the manufacturer.

## 13. Disposal considerations

### Waste information

Avoid contact of spilled material and runoff with soil and surface waterways. Consult an environmental professional to determine if local, regional or national regulations would classify spilled or contaminated materials as hazardous waste. Use only approved transporters, recyclers, treatment, storage or disposal facilities. Dispose of in accordance with all applicable local and national regulations.

Consult your local or regional authorities.

## 14. Transport information

Not classified as hazardous for transport (DOT, TDG, IMO/IMDG, IATA/ICAO)

## 15. Regulatory information

### U.S. Federal regulations

US INVENTORY (TSCA): In compliance.

This product is not regulated under Section 302 of SARA and 40 CFR Part 355.

SARA 311/312 MSDS distribution - chemical inventory - hazard identification: CASTROL ATF +4 : Immediate (Acute) Health Hazard

### SARA 313

#### Form R - Reporting requirements

This product does not contain any hazardous ingredients at or above regulated thresholds.

#### Supplier notification

This product does not contain any hazardous ingredients at or above regulated thresholds.

CERCLA Sections 102a/103 Hazardous Substances (40 CFR Part 302.4): Ethylbenzene: 1000 lbs. (453.6 kg); Aniline: 5000 lbs. (2268 kg); o-Toluidine: 100 lbs. (45.36 kg); Benzene: 10 lbs. (4.536 kg); Cadmium: 10 lbs. (4.536 kg); lead: 10 lbs. (4.536 kg); 2-Naphthylamine: 10 lbs. (4.536 kg); Arsenic: 1 lbs. (0.4536 kg);

### State regulations

No products were found.

Product name CASTROL ATF +4

Product code 464628-CA10

Page: 4/5

Version 2 Date of issue 08/14/2006.

Format US

Language ENGLISH.

Build 4.2.8

( ENGLISH )

**WARNING:** This product contains a chemical known to the State of California to cause cancer. Ethylbenzene; Aniline; o-Toluidine; 2-Naphthylamine; Arsenic

**WARNING:** This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm. Benzene; Cadmium; lead

**Inventories**

- AUSTRALIAN INVENTORY (AICS): Not listed.
- CANADA INVENTORY (DSL): In compliance.
- CHINA INVENTORY (IECS): In compliance.
- EC INVENTORY (EINECS/ELINCS): Not listed.
- JAPAN INVENTORY (ENCS): Not listed.
- KOREA INVENTORY (ECL): In compliance.
- PHILIPPINE INVENTORY (PICCS): In compliance.

---

**16. Other information**

**Label requirements**

CAUTION!

MAY CAUSE EYE IRRITATION.  
MAY CAUSE SKIN IRRITATION.  
MAY CAUSE RESPIRATORY TRACT IRRITATION.

**HMIS® Rating :**

<b>Health</b>	<b>1</b>	<b>-</b>	<b>National Fire Protection Association (U.S.A.)</b>
<b>Flammability</b>	<b>1</b>		
<b>Physical Hazard</b>	<b>0</b>		
<b>Personal protection</b>	<b>X</b>		



**History**

**Date of issue** 08/14/2006.  
**Date of previous issue** 02/06/2006.  
**Prepared by** Product Stewardship

**Notice to reader**

*NOTICE : This Material Safety Data Sheet is based upon data considered to be accurate at the time of its preparation. Despite our efforts, it may not be up to date or applicable to the circumstances of any particular case. We are not responsible for any damage or injury resulting from abnormal use, from any failure to follow appropriate practices or from hazards inherent in the nature of the product.*