

UTI COLOR Vinyl COLOR SPRAY

Thomas GREEN, Thomas GRAY, Blue Bird GREEN

MATERIAL SAFETY DATA SHEET

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME : SE SPRAYCAN SERIES
 IDENTIFICATION NUMBER: SE SPRAY
 PRODUCT USE/CLASS :
 DATE PRINTED: 12/19/05

SUPPLIER: Specialty Coatings & Chemicals Inc
 7360 Varna Ave.
 North Hollywood, CA 91605-4060
 Chemtrec: 1-800-424-9300
 24 Hour Emergency Hotline

MANUFACTURER: Specialty Coatings & Chemicals Inc
 7360 Varna Ave.
 North Hollywood, CA 91605-4060
 Chemtrec: 1-800-424-9300
 24 Hour Emergency Hotline

PREPARER: A.C. Macdonald, PHONE: 323-875-0233, PREPARE DATE: 12/10/04

SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

ITEM	CHEMICAL NAME	CAS NUMBER	WT/WT % LESS THAN
01	ISOBUTANE	68476-85-7	25.0 %
02	Acetone	67-64-1	25.0 %
03	2-BUTANONE	78-93-3	10.0 %
04	METHYL ISOBUTYL KETONE	108-10-1	10.0 %
05	PROPYLENE GLYCOL M ETHER ACETATE	108-65-6	5.0 %
06	TOLUOL	108-88-3	5.0 %

EXPOSURE LIMITS

ITEM	OSHA				COMPANY	
	TLV-TWA	TLV-STEL	PEL-TWA	PEL-CEILING	TLV-TWA	SKIN
01	N.E.	N.E.	N.E.	N.E.	N.E.	NO
02	750 ppm	250 ppm	750 ppm	N.E.	N.E.	NO
03	200 ppm	300 ppm	200 ppm	N.E.	200 ppm	NO
04	50 ppm	50 ppm	75 ppm	N.E.	N.E.	NO
05	N.E.	N.E.	N.E.	N.E.	N.E.	NO
06	100 ppm	150 ppm	100 ppm	500 ppm	N.E.	NO

(See Section 16 for abbreviation legend)

SECTION 3 - HAZARDS IDENTIFICATION

*** EMERGENCY OVERVIEW ***: No Information.

EFFECTS OF OVEREXPOSURE - EYE CONTACT: Liquid, aerosols and vapors of this product are irritating and can cause pain, tearing, reddening and swelling

(Continued on Page 2)

SECTION 3 - HAZARDS IDENTIFICATION

accompanied by a stinging sensation and/or a feeling like that of fine dust in the eyes. Severely irritating. If not removed promptly, will injure eye tissue, which may result in permanent damage.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

EFFECTS OF OVEREXPOSURE - INHALATION: Prolonged inhalation may be harmful. Reports have associated repeated and prolonged occupational overexposure to solvents with brain and nervous system damage. Intentional misuse by inhaling the contents may be harmful.

EFFECTS OF OVEREXPOSURE - INGESTION: This material may be harmful or fatal if swallowed.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: WARNING: This product contains xylene which contains benzene and toluene as impurities. Benzene and toluene are known to the State of California to cause cancer, or birth defects or other reproductive harm. The concentration of each of these impurities is expected to be less than 400 ppm.

PRIMARY ROUTE(S) OF ENTRY: SKIN CONTACT SKIN ABSORPTION INHALATION INGESTION EYE CONTACT

SECTION 4 - FIRST AID MEASURES

FIRST AID - EYE CONTACT: Immediately flush eyes with plenty of water. Get medical attention, if irritation persists.

FIRST AID - SKIN CONTACT: Wash with soap and water. Get medical attention if irritation develops or persists.

FIRST AID - INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

FIRST AID - INGESTION: If swallowed, induce vomiting immediately as directed by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately. Aspiration hazard if swallowed. If swallowed seek emergency medical attention.

SECTION 5 - FIRE FIGHTING MEASURES

FLASH POINT: 1 F (PENSKY-MARTENS C.C.)

LOWER EXPLOSIVE LIMIT: 0.9 % UPPER EXPLOSIVE LIMIT: 99.0 %

AUTOIGNITION TEMPERATURE:

SECTION 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: CO2 DRY CHEMICAL FOAM WATER FOG

UNUSUAL FIRE AND EXPLOSION HAZARDS: Vapors may form explosive mixture with air. Vapors can travel to a source of ignition and flash back. Extremely Flammable. Material will readily ignite at room temperatures. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. Empty drums should be completely drained, properly bunged and promptly returned to a drum reconitioner, or properly disposed of.

SPECIAL FIREFIGHTING PROCEDURES: Containers can build up pressure if exposed to heat (fire). As in any fire, wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear. Water runoff can cause environmental damage. Dike and collect water used to fight fire.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container. Avoid runoff into storm sewers and ditches which lead to waterways. Wear a self-contained breathing apparatus and appropriate personal protective equipment. (See Exposure Controls/Personal Protection Section)

SECTION 7 - HANDLING AND STORAGE

HANDLING: This product is to be used for industrial or professional uses only and is to be applied only by those who are trained in its safe and proper application. Employee education and training in the safe use and handling of this product is required; consult manufacturer if needed. When transferring material ground and bond containers and use spark proof tools and explosion proof equipment. Wash thoroughly after handling.

STORAGE: Keep away from heat, sparks and flame. Keep container closed when not in use.

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: Sufficient ventilation, in volume and pattern, could be provided to keep air contamination below current applicable OSHA permissible exposure limit or ACGHI's TLV limit. Good general ventilation should be sufficient to control airborne levels. Local exhaust ventilation may be necessary to control any air contaminants to within their TLVs during the use of this product. Use explosion-proof ventilation equipment. Facilities storing or utilizing this material should be equipped with an

(Continued on Page 4)

=====|
| SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION |
=====|

eyewash facility and a safety shower.

RESPIRATORY PROTECTION: A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

SKIN PROTECTION: Where contact is likely, wear chemical resistant gloves, a chemical suit, rubber boots, and chemical safety goggles plus a face shield. Use chemical splash goggles and face shield (ANSI Z87.1 or approved equivalent).

EYE PROTECTION: Wear safety glasses with side shields (or goggles) and a face shield.

OTHER PROTECTIVE EQUIPMENT: Where splashing is possible, full chemically resistant protective clothing (e.g. acid suit) and boots are required.

HYGIENIC PRACTICES: Follow all MSDS/label precautions even after container emptied because they may retain product residues.

=====|
| SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES |
=====|

BOILING RANGE	: -13 -- 302 F	VAPOR DENSITY	: Is heavier than air
ODOR	: Solvent	ODOR THRESHOLD	:
APPEARANCE	: Colored liquid	EVAPORATION RATE	: Is faster than Ether
SOLUBILITY IN H2O	: Partially soluble	SPECIFIC GRAVITY	: 0.1980
FREEZE POINT	:	pH @ 0.0 %	:
VAPOR PRESSURE	:	VISCOSITY	:
PHYSICAL STATE	:		
COEFFICIENT OF WATER/OIL DISTRIBUTION:			

(See Section 16 for abbreviation legend)

=====|
| SECTION 10 - STABILITY AND REACTIVITY |
=====|

CONDITIONS TO AVOID: No Information.

INCOMPATIBILITY: No Information.

HAZARDOUS DECOMPOSITION PRODUCTS: No Information.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

STABILITY: This product is stable under normal storage conditions.

(Continued on Page 5)

SECTION 11 - TOXICOLOGICAL PROPERTIES

No product or component toxicological information is available.

SECTION 12 - ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: No Information.

SECTION 13 - DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Dispose in accordance with State, local and Federal regulations.

SECTION 14 - TRANSPORTATION INFORMATION

No transportation information is available.

SECTION 15 - REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS: AS FOLLOWS -

OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200)

CERCLA - SARA HAZARD CATEGORY:

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

FIRE HAZARD. PRESSURIZED GAS HAZARD

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

CHEMICAL NAME	CAS NUMBER	WT/WT % IS LESS THAN
ISOBUTANE	68476-85-7	25.0 %
2-BUTANONE	78-93-3	10.0 %
METHYL ISOBUTYL KETONE	108-10-1	10.0 %
TOLUOL	108-88-3	5.0 %

TOXIC SUBSTANCES CONTROL ACT:

SECTION 15 - REGULATORY INFORMATION

TOXIC SUBSTANCES CONTROL ACT:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

CHEMICAL NAME	CAS NUMBER
No information is available.	

INTERNATIONAL REGULATIONS: AS FOLLOWS -

CANADIAN WHMIS: This MSDS has been prepared in compliance with Controlled Product Regulations except for use of the 16 headings.

CANADIAN WHMIS CLASS: No information available.

GOVERNMENT REGULATIONS: WARNING: This product contains xylene which contains benzene and toluene as impurities. Benzene and toluene are known to the State of California to cause cancer, birth defects or other reproductive harm.

SECTION 16 - OTHER INFORMATION

PIRATING RATINGS - HEALTH: 3 FLAMMABILITY: 4 REACTIVITY: 1

PREVIOUS MSDS REVISION DATE: 03/27/04

VOLATILE ORGANIC COMPOUNDS (VOCs): 0.81 lbs/gal, 97 grams/ltr

LEGEND: N.A. - Not Applicable, N.E. - Not Established,
N.D. - Not Determined

The information contained in this MSDS has been checked and should be accurate. However, it is the responsibility of the user to comply with all Federal, State, and Local laws and regulations.