	Page: 1
	Revision Date: 09/28/2016
<b>SAFETY DATA SHEET</b>	Print Date: 11/1/2016
	SDS Number: R0091437
Valvoline™ High Performance SAE 80W-90 Gear Oil ™ Trademark, Valvoline or its subsidiaries, regisred in various countries VV838	Version: 1.4

High performance SAE 80W-90  
Gear oil  
Valvoline

29 CFR 1910.1200 (OSHA HazCom 2012)

**SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**


**Product identifier**  
Trade name : Valvoline™ High Performance SAE 80W-90 Gear Oil  
  
™ Trademark, Valvoline or its subsidiaries, regisred in various countries

**Relevant identified uses of the substance or mixture and uses advised against**

<b>Details of the supplier of the safety data sheet</b> Valvoline LLC 3499 Blazer Parkway Lexington, KY 40509 United States of America (USA) 1-800-TEAMVAL	<b>Emergency telephone number</b> 1-800-VALVOLINE  <b>Regulatory Information Number</b> 1-800-TEAMVAL  <b>Product Information</b> 1-800-TEAMVAL
---------------------------------------------------------------------------------------------------------------------------------------------------------------------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------

**SECTION 2. HAZARDS IDENTIFICATION**


**GHS Classification**  
Skin sensitization : Category 1

**GHS label elements**  
Hazard pictograms : 

Signal Word : Warning

Hazard Statements : May cause an allergic skin reaction.

Precautionary Statements : **Prevention:**  
 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.  
 Contaminated work clothing must not be allowed out of the workplace.  
 Wear protective gloves.  
**Response:**  
 IF ON SKIN: Wash with plenty of soap and water.  
 If skin irritation or rash occurs: Get medical advice/ attention.  
 Wash contaminated clothing before reuse.  
**Disposal:**  
 Dispose of contents/ container to an approved waste disposal plant.

		Page: 2
<b>SAFETY DATA SHEET</b>		Revision Date: 09/28/2016
		Print Date: 11/1/2016
		SDS Number: R0091437
Valvoline™ High Performance SAE 80W-90 Gear Oil ™ Trademark, Valvoline or its subsidiaries, regisred in various countries VV838		Version: 1.4

**Other hazards**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

Chemical nature : Defatter


**Hazardous components**

Chemical name	CAS-No.	Classification	Concentration (%)
RESIDUAL OILS (PETROLEUM), SOLVENT-DEWAXED	64742-62-7	This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).	21.105
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT	64742-47-8	Asp. Tox. 1; H304	1.393
AMINES, C12-14-TERT-ALKYL	68955-53-3	Flam. Liq. 4; H227 Acute Tox. 4; H302 Acute Tox. 2; H330 Acute Tox. 3; H311 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317	0.343

**SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.

If inhaled : If breathed in, move person into fresh air.  
If unconscious, place in recovery position and seek medical advice.

		Page: 3
<b>SAFETY DATA SHEET</b>		Revision Date: 09/28/2016
		Print Date: 11/1/2016
		SDS Number: R0091437
Valvoline™ High Performance SAE 80W-90 Gear Oil ™ Trademark, Valvoline or its subsidiaries, regisred in various countries VV838		Version: 1.4


If symptoms persist, call a physician.

- In case of skin contact : Remove contaminated clothing. If irritation develops, get medical attention.  
If on skin, rinse well with water.  
First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.  
Wash contaminated clothing before re-use.
- In case of eye contact : Flush eyes with water as a precaution.  
Remove contact lenses.  
Protect unharmed eye.  
If eye irritation persists, consult a specialist.
- If swallowed : Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.  
Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:  
stomach or intestinal upset (nausea, vomiting, diarrhea)  
irritation (nose, throat, airways)  
Headache  
Dizziness  
May cause an allergic skin reaction.
- Notes to physician : No hazards which require special first aid measures.

---

## SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Water spray  
Foam

	Page: 4
	<b>SAFETY DATA SHEET</b>
	Revision Date: 09/28/2016
	Print Date: 11/1/2016
	SDS Number: R0091437
Valvoline™ High Performance SAE 80W-90 Gear Oil ™ Trademark, Valvoline or its subsidiaries, regisred in various countries VV838	Version: 1.4

Carbon dioxide (CO2)  
Dry chemical

- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : carbon dioxide and carbon monoxide  
Hydrocarbons
- Specific extinguishing methods :
- Product is compatible with standard fire-fighting agents.
- Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

---


#### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
- Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.
- Other information : Comply with all applicable federal, state, and local regulations.

---

#### SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Do not breathe vapours/dust.  
Do not smoke.  
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

		Page: 5
<b>SAFETY DATA SHEET</b>		Revision Date: 09/28/2016
		Print Date: 11/1/2016
		SDS Number: R0091437
Valvoline™ High Performance SAE 80W-90 Gear Oil ™ Trademark, Valvoline or its subsidiaries, regisred in various countries VV838		Version: 1.4

Container hazardous when empty.  
 Avoid exposure - obtain special instructions before use.  
 Avoid contact with skin and eyes.  
 Smoking, eating and drinking should be prohibited in the application area.  
 For personal protection see section 8.  
 Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.  
 Containers which are opened must be carefully resealed and kept upright to prevent leakage.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT	64742-47-8	TWA	5 mg/m3 Mist	OSHA Z-1
		TWA	200 mg/m3 (total hydrocarbon vapor)	ACGIH
		TWA	5 mg/m3 Mist	OSHA P0
		TWA	5 mg/m3 Mist	NIOSH REL
		ST	10 mg/m3 Mist	NIOSH REL
		PEL	5 mg/m3 particulate	CAL PEL

### Hazardous components without workplace control parameters


Components	CAS-No.
AMINES, C12-14-TERT-ALKYL	68955-53-3

**Engineering measures** : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

### Personal protective equipment

Respiratory protection : Respiratory protection is not required under normal conditions of use.

Hand protection


	Page: 6
	<b>SAFETY DATA SHEET</b>
	Revision Date: 09/28/2016
	Print Date: 11/1/2016
	SDS Number: R0091437
Valvoline™ High Performance SAE 80W-90 Gear Oil ™ Trademark, Valvoline or its subsidiaries, regisred in various countries VV838	Version: 1.4

- Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.
- Skin and body protection : Wear as appropriate:  
Impervious clothing  
Safety shoes  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.  
Discard gloves that show tears, pinholes, or signs of wear.  
Wear resistant gloves (consult your safety equipment supplier).
- Hygiene measures : Wash hands before breaks and at the end of workday.

---

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Physical state : liquid
- Colour : amber
- Odour : No data available
- Odour Threshold : No data available
- pH : No data available
- Melting point/freezing point : No data available
- Boiling point/boiling range : > 424.9 °F / 218.3 °C  
(1013.333 hPa)
- Flash point : > 222 °C  
Method: Cleveland open cup
- Evaporation rate : > 1  
Ethyl Ether
- Flammability (solid, gas) : No data available
- Upper explosion limit : No data available
- Lower explosion limit : No data available
- Vapour pressure : < 0.1000000 mmHg
- Relative vapour density : > 1AIR=1

	Page: 7
	<b>SAFETY DATA SHEET</b>
	Revision Date: 09/28/2016
	Print Date: 11/1/2016
	SDS Number: R0091437
Valvoline™ High Performance SAE 80W-90 Gear Oil ™ Trademark, Valvoline or its subsidiaries, regisred in various countries VV838	Version: 1.4

Relative density : 0.89 (60.00 °F)

Density : 0.8916 g/cm3 (15.56 °C)

Solubility(ies)

    Water solubility : No data available

    Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Thermal decomposition : No data available

Viscosity

    Viscosity, dynamic : No data available

    Viscosity, kinematic : 146 mm2/s (40 °C)

Oxidizing properties : No data available

---

#### SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous reactions : Product will not undergo hazardous polymerization.

Incompatible materials : Strong oxidizing agents


Hazardous decomposition products

Aldehydes  
carbon dioxide and carbon monoxide  
Carbon monoxide

---

#### SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation  
Skin contact  
Eye Contact  
Ingestion

	Page: 8
	SAFETY DATA SHEET
	Revision Date: 09/28/2016
	Print Date: 11/1/2016
	SDS Number: R0091437
Valvoline™ High Performance SAE 80W-90 Gear Oil ™ Trademark, Valvoline or its subsidiaries, regisred in various countries VV838	Version: 1.4

**Acute toxicity**

Not classified based on available information.

**Components:**

RESIDUAL OILS (PETROLEUM), SOLVENT-DEWAXED:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.58 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Assessment: Not classified as acutely toxic by inhalation under GHS.  
Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg  
Remarks: No mortality observed at this dose.

LD50 (Rabbit): > 2,000 mg/kg  
Assessment: Not classified as acutely toxic by dermal absorption under GHS.

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 3,160 mg/kg  
Assessment: No adverse effect has been observed in acute dermal toxicity tests.

AMINES, C12-14-TERT-ALKYL:

Acute oral toxicity : LD50 (Rat): 612 mg/kg  
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat, female): 1.19 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rat): 251 mg/kg  
Method: OECD Test Guideline 402

**Skin corrosion/irritation**

Not classified based on available information.

**Product:**

Remarks: May cause skin irritation in susceptible persons.

**Components:**


RESIDUAL OILS (PETROLEUM), SOLVENT-DEWAXED:

Species: Rabbit

Result: No skin irritation

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:



	Page: 9
	<b>SAFETY DATA SHEET</b>
	Revision Date: 09/28/2016
	Print Date: 11/1/2016
	SDS Number: R0091437
	Version: 1.4
Valvoline™ High Performance SAE 80W-90 Gear Oil ™ Trademark, Valvoline or its subsidiaries, regisred in various countries VV838	

Result: Slight, transient irritation

AMINES, C12-14-TERT-ALKYL:

Species: Rabbit

Result: Corrosive after 3 minutes to 1 hour of exposure

**Serious eye damage/eye irritation**

Not classified based on available information.

**Product:**

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

Remarks: Unlikely to cause eye irritation or injury.

**Components:**

RESIDUAL OILS (PETROLEUM), SOLVENT-DEWAXED:

Species: Rabbit

Result: No eye irritation

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:

Result: Slight, transient irritation

AMINES, C12-14-TERT-ALKYL:

Species: Rabbit

Result: Corrosive

**Respiratory or skin sensitisation**

Skin sensitisation: May cause an allergic skin reaction.

Respiratory sensitisation: Not classified based on available information.

**Components:**

RESIDUAL OILS (PETROLEUM), SOLVENT-DEWAXED:

Test Type: Buehler Test

Species: Guinea pig

Assessment: Does not cause skin sensitisation.

AMINES, C12-14-TERT-ALKYL:

Test Type: Buehler Test

Species: Guinea pig

Assessment: The product is a skin sensitiser, sub-category 1A.

Germ cell mutagenicity

Not classified based on available information.

**Components:**

AMINES, C12-14-TERT-ALKYL:

Genotoxicity in vitro

: Test Type: Ames test

Test species: Salmonella typhimurium

Metabolic activation: with and without metabolic activation


Method: OECD Test Guideline 471

Result: negative

Genotoxicity in vivo

: Test Type: Micronucleus test

Test species: Mouse

	Page: 10
	<b>SAFETY DATA SHEET</b>
	Revision Date: 09/28/2016
	Print Date: 11/1/2016
	SDS Number: R0091437
Valvoline™ High Performance SAE 80W-90 Gear Oil ™ Trademark, Valvoline or its subsidiaries, regisred in various countries VV838	Version: 1.4

Cell type: Bone marrow  
Method: OECD Test Guideline 474  
Result: negative

**Carcinogenicity**

Not classified based on available information.

**Reproductive toxicity**

Not classified based on available information.

**STOT - single exposure**

Not classified based on available information.

**STOT - repeated exposure**

Not classified based on available information.

**Aspiration toxicity**

Not classified based on available information.

**Product:**

No aspiration toxicity classification

**Components:**

RESIDUAL OILS (PETROLEUM), SOLVENT-DEWAXED:

No aspiration toxicity classification

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:

May be fatal if swallowed and enters airways.

**Further information**

**Product:**

Remarks: No data available

**SECTION 12. ECOLOGICAL INFORMATION**

**Ecotoxicity**

**Product:**

Ecotoxicology Assessment

Acute aquatic toxicity : Acute aquatic toxicity Category 3; Harmful to aquatic life.


Chronic aquatic toxicity : Chronic aquatic toxicity Category 3; Harmful to aquatic life with long lasting effects.

**Components:**

RESIDUAL OILS (PETROLEUM), SOLVENT-DEWAXED:


Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)); > 100 mg/l  
Exposure time: 96 h  
Test Type: static test  
Test substance: WAF  
Method: OECD Test Guideline 203  
Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)); > 10,000 mg/l  
Exposure time: 48 h  
Test Type: static test  
Test substance: WAF

	Page: 11
	<b>SAFETY DATA SHEET</b>
	Revision Date: 09/28/2016
	Print Date: 11/1/2016
	SDS Number: R0091437
Valvoline™ High Performance SAE 80W-90 Gear Oil ™ Trademark, Valvoline or its subsidiaries, regisred in various countries VV838	Version: 1.4

Method: OECD Test Guideline 202

- Toxicity to algae : NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l  
End point: Growth inhibition  
Exposure time: 72 h  
Test Type: static test  
Test substance: WAF  
Method: OECD Test Guideline 201
- Toxicity to fish (Chronic toxicity) : NOELR (Oncorhynchus mykiss (rainbow trout)): Calculated >= 1,000 mg/l  
Exposure time: 14 d
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEL (Daphnia (water flea)): 10 mg/l  
Exposure time: 21 d  
Test substance: WAF  
Method: OECD Test Guideline 211
- DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:  
Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2 - 5 mg/l  
Exposure time: 96 h  
Test Type: semi-static test  
Test substance: WAF  
Method: OECD Test Guideline 203  
Remarks: Information given is based on data obtained from similar substances.
- Toxicity to daphnia and other aquatic invertebrates : EL50 (Water flea (Daphnia magna)): 1.4 mg/l  
Exposure time: 48 h  
Test Type: static test  
Test substance: WAF  
Method: OECD Test Guideline 202  
Remarks: Information given is based on data obtained from similar substances.
- Toxicity to algae : EL50 (Pseudokirchneriella subcapitata (green algae)): > 1 - 3 mg/l  
Exposure time: 72 h  
Test Type: static test  
Test substance: WAF  
Method: OECD Test Guideline 201  
Remarks: Information given is based on data obtained from similar substances.
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEL (Water flea (Daphnia magna)): 0.48 mg/l  
Exposure time: 21 d  
Test Type: semi-static test  
Test substance: WAF  
Method: OECD Test Guideline 211  
Remarks: Information given is based on data obtained from similar substances.

	Page: 12
	<b>SAFETY DATA SHEET</b>
	Revision Date: 09/28/2016
	Print Date: 11/1/2016
	SDS Number: R0091437
Valvoline™ High Performance SAE 80W-90 Gear Oil ™ Trademark, Valvoline or its subsidiaries, regisred in various countries VV838	Version: 1.4

**AMINES, C12-14-TERT-ALKYL:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 1.3 mg/l  
Exposure time: 96 h  
Test Type: static test  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Water flea (Daphnia magna)): 2.5 mg/l  
Exposure time: 48 h  
Test Type: static test

Toxicity to algae : ErC50 (Pseudokirchneriella subcapitata (microalgae)): 0.44 mg/l  
End point: Growth inhibition  
Exposure time: 72 h  
Test Type: static test  
Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (microalgae)): 0.05 mg/l  
End point: Growth inhibition  
Exposure time: 72 h  
Test Type: static test  
Method: OECD Test Guideline 201

M-Factor (Acute aquatic toxicity) : 1

Toxicity to fish (Chronic toxicity) : NOEC (Oncorhynchus mykiss (rainbow trout)): 0.078 mg/l  
Exposure time: 96 d  
Test Type: flow-through test  
Method: OECD Test Guideline 210

M-Factor (Chronic aquatic toxicity) : 1

**Persistence and degradability**

**Components:**


**RESIDUAL OILS (PETROLEUM), SOLVENT-DEWAXED:**

Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 2 - 4 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301B

**DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:**

Biodegradability : Result: Inherently biodegradable  
Biodegradation: 58.6 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F

Remarks: Expected to be biodegradable

		Page: 13
<b>SAFETY DATA SHEET</b>		Revision Date: 09/28/2016
		Print Date: 11/1/2016
		SDS Number: R0091437
Valvoline™ High Performance SAE 80W-90 Gear Oil ™ Trademark, Valvoline or its subsidiaries, regisred in various countries VV838		Version: 1.4

**AMINES, C12-14-TERT-ALKYL:**  
**Biodegradability** : Result: Not readily biodegradable.  
 Biodegradation: 22 %  
 Exposure time: 28 d  
 Method: OECD Test Guideline 301D

No data available  
**Bioaccumulative potential**

**Components:**  
**AMINES, C12-14-TERT-ALKYL:**  
 Partition coefficient: n-octanol/water : log Pow: 2.9

No data available

**Mobility in soil**

**Components:**

No data available

**Other adverse effects**

No data available

**Product:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Harmful to aquatic life with long lasting effects.

**Components:**

### SECTION 13. DISPOSAL CONSIDERATIONS

**Disposal methods**


**General advice** : The product should not be allowed to enter drains, water courses or the soil.  
 Do not contaminate ponds, waterways or ditches with chemical or used container.  
 Send to a licensed waste management company.  
 Dispose of in accordance with all applicable local, state and federal regulations.

**Contaminated packaging** : Empty remaining contents.  
 Dispose of as unused product.  
 Empty containers should be taken to an approved waste handling site for recycling or disposal.  
 Do not re-use empty containers.

### SECTION 14. TRANSPORT INFORMATION

**International transport regulations**

**REGULATION**

	Page: 14
<b>SAFETY DATA SHEET</b>	Revision Date: 09/28/2016
	Print Date: 11/1/2016
	SDS Number: R0091437
Valvoline™ High Performance SAE 80W-90 Gear Oil ™ Trademark, Valvoline or its subsidiaries, registered in various countries VV838	Version: 1.4

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.
-----------	----------------------	---------------	--------------------	---------------	------------------------------

**U.S. DOT - ROAD**

Not dangerous goods
---------------------

**CFR\_RAIL\_C**

Not dangerous goods
---------------------

**U.S. DOT - INLAND WATERWAYS**

Not dangerous goods
---------------------

**TDG\_ROAD\_C**

Not dangerous goods
---------------------

**TDG\_RAIL\_C**

Not dangerous goods
---------------------

**TDG\_INWT\_C**

Not dangerous goods
---------------------

**INTERNATIONAL MARITIME DANGEROUS GOODS**

Not dangerous goods
---------------------

**INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO**

Not dangerous goods
---------------------

**INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER**


Not dangerous goods
---------------------

**MX\_DG**

Not dangerous goods
---------------------

\*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Marine pollutant	no
------------------	----

		Page: 15
<b>SAFETY DATA SHEET</b>		Revision Date: 09/28/2016
		Print Date: 11/1/2016
		SDS Number: R0091437
Valvoline™ High Performance SAE 80W-90 Gear Oil ™ Trademark, Valvoline or its subsidiaries, regisred in various countries VV838		Version: 1.4

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

## SECTION 15. REGULATORY INFORMATION

**SARA 311/312 Hazards** : Acute Health Hazard

**SARA 313** This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

**California Prop 65** This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

**The components of this product are reported in the following inventories:**

TSCA : On TSCA Inventory

DSL : All components of this product are on the Canadian DSL

AICS : On the inventory, or in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

**Inventories**


AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)


## SECTION 16. OTHER INFORMATION

**Further information**

Revision Date: 09/28/2016

<b>NFPA:</b>	<b>HMIS III:</b>
--------------	------------------

	Page: 16
	Revision Date: 09/28/2016
<b>SAFETY DATA SHEET</b>	Print Date: 11/1/2016
	SDS Number: R0091437
Valvoline™ High Performance SAE 80W-90 Gear Oil ™ Trademark, Valvoline or its subsidiaries, registered in various countries VV838	Version: 1.4

<p>Flammability</p>  <p>Health</p> <p>Instability</p> <p>Special hazard.</p>	<table border="1"> <tr> <td><b>HEALTH</b></td> <td style="text-align: center;"><b>2</b></td> </tr> <tr> <td><b>FLAMMABILITY</b></td> <td style="text-align: center;"><b>1</b></td> </tr> <tr> <td><b>PHYSICAL HAZARD</b></td> <td style="text-align: center;"><b>0</b></td> </tr> </table> <p>0 = not significant, 1 = Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic</p>	<b>HEALTH</b>	<b>2</b>	<b>FLAMMABILITY</b>	<b>1</b>	<b>PHYSICAL HAZARD</b>	<b>0</b>
<b>HEALTH</b>	<b>2</b>						
<b>FLAMMABILITY</b>	<b>1</b>						
<b>PHYSICAL HAZARD</b>	<b>0</b>						

**NFPA Flammable and Combustible Liquids Classification**  
Combustible Liquid Class IIIB

**Full text of H-Statements**

- |      |                                               |
|------|-----------------------------------------------|
| H227 | Combustible liquid.                           |
| H302 | Harmful if swallowed.                         |
| H304 | May be fatal if swallowed and enters airways. |
| H311 | Toxic in contact with skin.                   |
| H314 | Causes severe skin burns and eye damage.      |
| H317 | May cause an allergic skin reaction.          |
| H318 | Causes serious eye damage.                    |
| H330 | Fatal if inhaled.                             |


Sources of key data used to compile the Safety Data Sheet  
Valvoline internal data including own and sponsored test reports  
The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

- ACGIH : American Conference of Industrial Hygienists
- BEI : Biological Exposure Index
- CAS : Chemical Abstracts Service (Division of the American Chemical Society).
- CMR : Carcinogenic, Mutagenic or Toxic for Reproduction
- FG : Food grade



		Page: 17
<b>SAFETY DATA SHEET</b>		Revision Date: 09/28/2016
		Print Date: 11/1/2016
		SDS Number: R0091437
Valvoline™ High Performance SAE 80W-90 Gear Oil ™ Trademark, Valvoline or its subsidiaries, regisred in various countries VV838		Version: 1.4

GHS : Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA : International Air Transport Association.

IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization

ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"

IMDG : International Maritime Code for Dangerous Goods

ISO : International Organization for Standardization

logPow : octanol-water partition coefficient

LCxx : Lethal Concentration, for xx percent of test population

LDxx : Lethal Dose, for xx percent of test population.

ICxx : Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx

N.O.S.: Not Otherwise Specified

OECD : Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit

P-Statement : Precautionary Statement

PBT : Persistent , Bioaccumulative and Toxic

PPE : Personal Protective Equipment

STEL : Short-term exposure limit

STOT : Specific Target Organ Toxicity

TLV : Threshold Limit Value

TWA : Time-weighted average

vPvB : Very Persistent and Very Bioaccumulative

WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act

DOT : Department of Transportation

FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act

HMIRC : Hazardous Materials Information Review Commission

HMIS : Hazardous Materials Identification System

NFPA : National Fire Protection Association

NIOSH : National Institute for Occupational Safety and Health

OSHA : Occupational Safety and Health Administration

PMRA : Health Canada Pest Management Regulatory Agency

RTK : Right to Know

WHMIS : Workplace Hazardous Materials Information System