# SAFETY DATA SHEET



10/17/16

Master Plumber YELLOW FORMULG 55 Thread Seal

1. Identification

**Product identifier** 

**Harvey Seal** 

Other means of identification

**Product code** 

3703E

**Synonyms** 

Part Numbers: 025020, 025050, 025080

Recommended use

Pipe Joint Compound for Threaded Metal Pipes

Recommended restrictions

None known.

Manufacturer/Importer/Supplier/Distributor information

Company Name

William H. Harvey Company 4334 South 67th Street

Address

Omaha, NE 68117

Telephone

402-331-115

E-mail

info@oatey.com

**Transport Emergency** 

Chemtrec 1-800-424-9300 (Outside the US 1-703-527-3887)

**Emergency First Aid** 

1-877-740-5015

Contact person

MSDS Coordinator

# 2. Hazard(s) identification

Physical hazards

Not classified.

Health hazards

Not classified.

**OSHA** defined hazards

Not classified.

Label elements

Hazard symbol

None.

Signal word

None.

**Hazard statement** 

The mixture does not meet the criteria for classification.

Precautionary statement

Prevention

Observe good industrial hygiene practices.

Response

Wash hands after handling.

Storage

Store away from incompatible materials.

Disposal

Dispose of waste and residues in accordance with local authority requirements.

Hazard(s) not otherwise

classified (HNOC)

Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

# 3. Composition/information on ingredients

### **Mixtures**

Chemical name		CAS number	%
Calcium carbonate		1317-65-3	60-70
Oxidized Soy Bean Oil	 and the second s	68152-81-8	10-20
2-Butoxyethanol		111-76-2	5-10
Silicon Dioxide		112926-00-8	1-5
Crystalline silica (Quartz)	 	14808-60-7	< 1.5

<sup>\*</sup>Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

#### 4. First-aid measures

Inhalation

Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact

Wash off with soap and water. Get medical attention if irritation develops and persists.

Harvey Seal

SDS US 1/8 Eye contact

Rinse with water. Get medical attention if irritation develops and persists.

Ingestion

Rinse mouth. Get medical attention if symptoms occur.

Most important

symptoms/effects, acute and

delayed

Indication of immediate

medical attention and special treatment needed

Treat symptomatically.

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

# 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Fire fighting equipment/instructions

Specific methods General fire hazards Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Move containers from fire area if you can do so without risk.

Use standard firefighting procedures and consider the hazards of other involved materials.

No unusual fire or explosion hazards noted.

### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Methods and materials for containment and cleaning up Keep unnecessary personnel away. For personal protection, see section 8 of the SDS.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

**Environmental precautions** 

Avoid discharge into drains, water courses or onto the ground.

# 7. Handling and storage

Precautions for safe handling

Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure.

Conditions for safe storage. including any incompatibilities Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

# 8. Exposure controls/personal protection

### Occupational exposure limits

### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form	
2-Butoxyethanol (CAS	PEL	240 mg/m3		
111-76-2)		50 ppm		
Calcium carbonate (CAS	PEL	5 mg/m3	Respirable fraction.	
1317-65-3)		15 mg/m3	Total dust.	
US. OSHA Table Z-3 (29 CFR 1910.100	00)			
Components	Type	Value	Form	
Crystalline silica (Quartz) (CAS 14808-60-7)	TWA	0.3 mg/m3	Total dust	
(676 14000-00-7)		0.1 mg/m3	Respirable.	

### US. OSHA Table Z-3 (29 CFR 1910.1000)

Components		Type			Value	Form
Silicon Dioxide (CAS		TWA			0.8 mg/m3	
112926-00-8)					20 mppcf	
US. ACGIH Threshold Lir	mit Values				20 Hippoi	
US. AUGIN THIESHOU LII	iiit values					
Components		Type			Value	Form
2-Butoxyethanol (CAS 111-76-2)		TWA			20 ppm	
Crystalline silica (Quartz) (CAS 14808-60-7)		TWA			0.025 mg/m3	Respirable fraction.
US. NIOSH: Pocket Guide	e to Chemical Haza	ards				
Components		Туре			Value	Form
2-Butoxyethanol (CAS 111-76-2)		TWA			24 mg/m3	
111-70-2)					5 ppm	
Calcium carbonate (CAS 1317-65-3)	•	TWA			5 mg/m3	Respirable.
					10 mg/m3	Total
Crystalline silica (Quartz) (CAS 14808-60-7)		TWA			0.05 mg/m3	Respirable dust.
Silicon Dioxide (CAS 112926-00-8)		TWA			6 mg/m3	
ogical limit values						
ACGIH Biological Exposu	ure Indices					
Components	Value		Determinant	Specimer	sampling Time	
2-Butoxyethanol (CAS 111-76-2)	200 mg/g		Butoxyacetic acid (BAA),	Creatinine in urine	*	

<sup>\* -</sup> For sampling details, please see the source document.

# **Exposure guidelines**

US - California OELs: Skin designation

2-Butoxyethanol (CAS 111-76-2)

Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

2-Butoxyethanol (CAS 111-76-2)

Skin designation applies.

with hydrolysis

US - Tennessee OELs: Skin designation

2-Butoxyethanol (CAS 111-76-2)

Can be absorbed through the skin.

US. NIOSH: Pocket Guide to Chemical Hazards

2-Butoxyethanol (CAS 111-76-2)

Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

2-Butoxyethanol (CAS 111-76-2)

Can be absorbed through the skin.

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If

exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection

Wear appropriate chemical resistant gloves.

Other

Wear suitable protective clothing.

Respiratory protection

Use a particulate filter respirator for particulate concentrations exceeding the Occupational

Exposure Limit.

Wear appropriate thermal protective clothing, when necessary. Thermal hazards

Harvey Seal

SDS US

924490 Version #: 01 Revision date: -Issue date: 05-February-2015 General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

### 9. Physical and chemical properties

**Appearance** 

Physical state

Liquid.

**Form** 

Liquid Liquid paste.

Color

Yellow.

Odor

Petroleum.

Odor threshold

Not available.

рH

Not available.

Melting point/freezing point

Not available.

Initial boiling point and boiling

Not available.

range

Flash point

153.0 °F (67.2 °C)

**Evaporation rate** 

Not available.

Flammability (solid, gas)

Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit - upper

Not available.

(%)

Explosive limit - lower (%)

Not available.

Explosive limit - upper (%)

Not available.

Vapor pressure

Not available.

Vapor density

> 1

Relative density

Not available.

Solubility(ies)

Solubility (water)

Not available.

Partition coefficient

(n-octanol/water)

Not available.

Auto-ignition temperature

Not available. Not available.

**Decomposition temperature** 

Viscosity

30000 cP

Other information

VOC (Weight %)

119 g/l

### 10. Stability and reactivity

Reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability

Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid

Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials

Acids. Strong oxidizing agents. Fluorine.

Hazardous decomposition products

No hazardous decomposition products are known.

# 11. Toxicological information

# Information on likely routes of exposure

Inhalation

Prolonged inhalation may be harmful.

Skin contact

2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.

Harvey Seal

SDS US

924490 Version #: 01 Revision date: -Issue date: 05-February-2015 Eye contact

Direct contact with eyes may cause temporary irritation.

Ingestion

Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

Information on toxicological effects

**Acute toxicity** 

Components Species Test Results

Silicon Dioxide (CAS 112926-00-8)

Acute Oral

LD50

Rat

> 22500 mg/kg

\* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation

Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

irritation

Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization

Not a respiratory sensitizer.

Skin sensitization

This product is not expected to cause skin sensitization.

Germ cell mutagenicity

No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity

In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.)

#### IARC Monographs. Overall Evaluation of Carcinogenicity

2-Butoxyethanol (CAS 111-76-2)

Crystalline silica (Quartz) (CAS 14808-60-7)

Silicon Dioxide (CAS 112926-00-8)

3 Not classifiable as to carcinogenicity to humans.

1 Carcinogenic to humans.

3 Not classifiable as to carcinogenicity to humans.

**NTP Report on Carcinogens** 

Crystalline silica (Quartz) (CAS 14808-60-7)

Known To Be Human Carcinogen.

#### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity

This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

**Aspiration hazard** 

Not an aspiration hazard.

**Chronic effects** 

May be harmful if absorbed through skin. Prolonged inhalation may be harmful.

2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and

prolonged. These effects have not been observed in humans.

Prolonged exposure may cause chronic effects.

**Further information** 

This product has no known adverse effect on human health.

### 12. Ecological information

**Ecotoxicity** 

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability

Bioaccumulative potential

No data is available on the degradability of this product.

Harvey Seal

SDS US

924490 Version #: 01 Revision date: - Issue date: 05-February-2015

5/8

#### Partition coefficient n-octanol / water (log Kow)

2-Butoxyethanol (CAS 111-76-2)

0.83

Mobility in soil

No data available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

### 13. Disposal considerations

**Disposal instructions** 

Collect and reclaim or dispose in sealed containers at licensed waste disposal site.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

# 14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

**IMDG** 

Not regulated as dangerous goods.

Transport in bulk according to

Annex II of MARPOL 73/78 and

the IBC Code

**General information** 

Not established.

DOT: Not regulated as dangerous goods except when shipped in bulk. This material is not

regulated if in a container of 119 gallon (450 L) capacity or less.

### 15. Regulatory information

**US federal regulations** 

All components are on the U.S. EPA TSCA Inventory List.

This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard

Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

2-Butoxyethanol (CAS 111-76-2)

LISTED

# Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate Hazard - No Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

No

chemical

SARA 313 (TRI reporting)

Chemical nameCAS number% by wt.2-Butoxyethanol111-76-25-10

### Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Harvey Seal

SDS US

924490 Version #: 01 Revision date: - Issue date: 05-February-2015

### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

### **US state regulations**

#### US. Massachusetts RTK - Substance List

2-Butoxyethanol (CAS 111-76-2) Calcium carbonate (CAS 1317-65-3) Crystalline silica (Quartz) (CAS 14808-60-7)

Silicon Dioxide (CAS 112926-00-8).

### US. New Jersey Worker and Community Right-to-Know Act

2-Butoxyethanol (CAS 111-76-2) Calcium carbonate (CAS 1317-65-3) Crystalline silica (Quartz) (CAS 14808-60-7) Silicon Dioxide (CAS 112926-00-8)

# US. Pennsylvania Worker and Community Right-to-Know Law

2-Butoxyethanol (CAS 111-76-2) Calcium carbonate (CAS 1317-65-3) Crystalline silica (Quartz) (CAS 14808-60-7)

#### US. Rhode Island RTK

2-Butoxyethanol (CAS 111-76-2)

#### **US. California Proposition 65**

WARNING: This product contains a chemical known to the State of California to cause cancer.

### US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Crystalline silica (Quartz) (CAS 14808-60-7)

#### International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

<sup>\*</sup>A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

# 16. Other information, including date of preparation or last revision

Issue date 05-February-2015

Revision date Version # 01

Health: 0 **HMIS®** ratings Flammability: 2

Physical hazard: 0

NFPA ratings



924490 Version #: 01 Revision date: - Issue date: 05-February-2015 7/8

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing

#### Disclaimer

William H. Harvey Company cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.