

Section 1 - Product Identification



Western Automotive Finishes
101 Prospect Ave. N.W.
Cleveland, OH 44115

Material Safety Data Sheet

Emergency telephone number
information telephone number
Date of preparation

(216) 566-2917
(216) 566-2902
December 10, 1999

©1999, Western Automotive Finishes

DIMENSION™ Reducers

DR600/W1

CAS No.	Section 2 - Hazardous Ingredients (percent by weight)	ACGIH TLV <STEL>	OSHA PEL <STEL>	Units	Vapor Pressure (mm Hg)	DR631 Fast	DR632 Fast/Medium	DR633 Medium	DR634 Medium/Slow	DR635 Slow	DR636 Very Slow
108-88-3	§ Toluene.	50	100	PPM (Skin)	22.0	26					
98-56-6	p-Chlorobenzotrifluoride.	Not Established			5.3						13
67-64-1	Acetone.	500	1000	PPM	180.0	29	28	29	29	24	23
78-93-3	§ Methyl Ethyl Ketone.	200	200	PPM	70.0	43	24	10	10		
5440-89-1	5-Ethyl-2-nonanone	<300>	<300>							3	9
927-49-1	Diamyl Ketone.	Not Established								2	8
110-43-0	Methyl n-Amyl Ketone.	50	100	PPM	2.1		5	24	49	51	14
763-69-9	Ethyl 3-Ethoxypropionate.	Not Established			1.1		6	6	8		
123-86-4	n-Butyl Acetate.	150	150	PPM	10.0		36	31			
112-07-2	§ 2-Butoxyethyl Acetate.	Not Established			1.0				3	19	31
	Weight per Gallon (lbs.)					6.78	6.94	6.92	6.82	6.91	7.48
	VOC (Volatile Organic Compounds) Total - lbs./gal.					4.80	4.96	4.94	4.83	5.26	4.76
	VOC Less Water & Federally Exempt Solvents - lbs./gal.					6.86	7.08	7.06	6.91	7.02	7.33
	Photochemically Reactive					Yes	No	No	No	No	No
	Flash Point (°F)					20	20	20	20	20	20
	HMIS (NTPA) Rating (health - flammability - reactivity)					2-3-0	2-3-0	2-3-0	2-3-0	2-3-0	2*-3-0
	PAINT-SAFE® Personal Protection					J3	J3	J3	J3	J3	J3

§ Ingredient subject to the reporting requirements of the Superfund Amendments and Reauthorization Act (SARA) Section 313, 40 CFR 372.65 C

DIMENSION™ Reducers

DR600/W1

Section 3 — Physical Data

PRODUCT WEIGHT See TABLE
SPECIFIC GRAVITY 0.82-0.90
BOILING RANGE 132-454 °F
VOLATILE VOLUME 99 %

EVAPORATION RATE Slower than Ether
VAPOR DENSITY Heavier than Air
MELTING POINT N.A.
SOLUBILITY IN WATER N.A.

Section 4 — Fire And Explosion Hazard Data

FLAMMABILITY CLASSIFICATION FLASH POINT See TABLE
RED LABEL -- Extremely Flammable, Flash below 21 °F

LEL 0.5 UEL 12.8

EXTINGUISHING MEDIA

Carbon Dioxide, Dry Chemical, Foam

UNUSUAL FIRE AND EXPLOSION HAZARDS

Keep containers tightly closed. Isolate from heat, electrical equipment, sparks, and open flame. Closed containers may explode when exposed to extreme heat. Application to hot surfaces requires special precautions. During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

SPECIAL FIRE FIGHTING PROCEDURES

Full protective equipment including self-contained breathing apparatus should be used. Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

Section 5 — Health Hazard Data

ROUTES OF EXPOSURE

Exposure may be by INHALATION and/or SKIN or EYE contact, depending on conditions of use. Alcohols and acetates can be absorbed through the skin. Follow recommendations for proper use, ventilation, and personal protective equipment to minimize exposure.

ACUTE Health Hazards

EFFECTS OF OVEREXPOSURE

Irritation of eyes, skin and respiratory system. May cause nervous system depression. Extreme overexposure may result in unconsciousness and possibly death.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

Headache, dizziness, nausea, and loss of coordination are indications of excessive exposure to vapors or spray mists.

Redness and itching or burning sensation may indicate eye or excessive skin exposure.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

None generally recognized.

EMERGENCY AND FIRST AID PROCEDURES

If INHALED: If affected, remove from exposure. Restore breathing. Keep warm and quiet. Wash affected area thoroughly with soap and water.

If on SKIN: Remove contaminated clothing and launder before re-use.

If in EYES: Flush eyes with large amounts of water for 15 minutes. Get medical attention.

If SWALLOWED: DR631 =>

Never give anything by mouth to an unconscious person.

DO NOT INDUCE VOMITING. Give conscious patient several glasses of water. Seek medical attention.

Other Products => Get medical attention

CHRONIC Health Hazards

No ingredient in these products is an IARC, NTP or OSHA listed carcinogen.

Methyl Ethyl Ketone may increase the nervous system effects of other solvents.

Prolonged overexposure to solvent ingredients in the following products may cause adverse effects to organ systems:

* DR635, DR636 liver, urinary & blood forming

* DR632, DR633 & DR634 liver, urinary, blood forming & reproductive

* DR631 liver, urinary, cardiovascular & reproductive

Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

and nervous system damage.

and nervous system damage.

and nervous system damage.

and nervous system damage.

and nervous system damage.

and nervous system damage.

and nervous system damage.

and nervous system damage.

and nervous system damage.

and nervous system damage.

and nervous system damage.

and nervous system damage.

and nervous system damage.

Section 7 — Spill Or Leak Procedures

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Remove all sources of ignition. Ventilate and remove with inert absorbent.

WASTE DISPOSAL METHOD

Waste from these products may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers. Waste from products containing Methyl Ethyl Ketone may also require extractability testing.

Incinerate in approved facility. Do not incinerate closed container. Dispose of in accordance with Federal, State, and Local regulations regarding pollution.

Section 8 — Protection Information

PRECAUTIONS TO BE TAKEN IN USE

Use only with adequate ventilation. Avoid breathing vapor and spray mist. Avoid contact with skin and eyes. Wash hands after using.

VENTILATION

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

RESPIRATORY PROTECTION

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2.

PROTECTIVE GLOVES

Wear gloves which are recommended by glove supplier for protection against materials in Section 2.

EYE PROTECTION

Wear safety spectacles with unperforated sideshields.

Section 9 — Precautions

DOL STORAGE CATEGORY - 1B

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Contents are EXTREMELY FLAMMABLE. Keep away from heat, sparks, and open flame. Vapors will accumulate readily and may ignite explosively.

During use and until all vapors are gone: Keep area ventilated - Do not smoke - Extinguish all flames, pilot lights, and heaters - Turn off stoves, electric tools and appliances, and any other sources of ignition.

Consult NFPA Code. Use approved Bonding and Grounding procedures.

Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally. Keep out of the reach of children.

OTHER PRECAUTIONS

Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

Section 10 — Other Regulatory Information

CALIFORNIA PROPOSITION 65

WARNING: These products contain chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

TSCA CERTIFICATION

All chemicals in these products are listed, or are exempt from listing, on the TSCA Inventory.

Section 6 — Reactivity Data

STABILITY - Stable

CONDITIONS TO AVOID - None known.

INCOMPATIBILITY - - - None known.

HAZARDOUS DECOMPOSITION PRODUCTS

By fire: Carbon Dioxide, Carbon Monoxide

HAZARDOUS POLYMERIZATION - Will Not Occur

The above information pertains to these products as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to these products may substantially alter the composition and hazards of the products. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.